Materials & Tools

□ Fabric: 90cm x 1.5m

□ Double sided bias binding tape: 2cm wide x 1.7m

Fabric shown for this sample: LO-41010-2B

Shoulder Tuck Blouse

Design & work: Anriko

Size: Back Length 62cm Body width 60cm

Cutting Layout

Add 1cm seam unless specified otherwise.

Instructions Front Side - (FrS), Reverse Side (RvS)

made in different fabrics) featured in kokka-fabric.com.

Front body 150 0.7 O.7 Yoke 0.7 Yoke 0.7 Hem 4

1. Make the tuck

2 Fold the tuck and baste.

1. Make the tuck

3 Fold the tuck and baste.

Tuck position

Tuck position

Front body

(FrS)

(RvS)

3 Run zigza

2. Make the gathering

The craft projects and works featured in kokka-fabric.com are strictly for personal use and enjoyment. Please refrain from selling handmade items using the same exact design (including the pieces

② Pull the thread and shrink to the patterned dimension.

③ Run rough stitches on the seam where gathering is applied.

Back body (FrS)

3. Make the back body

① With the front sides facing each other, sew together the yoke and back body.

② Apply stitches on the seam.

3 Run zigzag stitches on the seam.

Yoke
(FrS)

Back body
(RvS)

4. Finish the neckline

90

① With the front sides facing each other, sew together the front body and yoke at the shoulder. Apply zigzag stitches on the seam and press it down to the back side.

② With the front sides facing outside, fold the bias binding tape in half. Place the seam in-between and sew.

Place the seam in-between and seam in-between

③ Press down ② to the reverse side and sew the back.

 Fold the seam of the hem in three.

5. Finish the shirt

Bias binding tape
(FrS)

4 As in 423, finish both armholes.

Front body
(FrS)

2 Unfold the seam of the hem. With the front sides facing each other, sew the sides together. Apply zigzag stitches on the seam and press it down to the back side.

3 Fold the seam of the hem in three and sew.

