kokka-fabric.com



## **Clutch Bag**

Size: About 32cm (I) x About 25cm (w)

## Instructions

Bottom fabric (reverse side)

Front bag fabric (front/outer side)

Sew the bottom fabric to outer fabric A.

With front/outer sides facing

outer fabric B together.

each other, sew the zipper and

Bottom fabric -

(front/outer side)

Run a stitch at 0.2cm from the edge. <

1. Attach fusible interfacing to the reverse side of the front and back bag fabrics.

Sew the bottom fabric to the front bag fabric (Outer fabric A).

Fold for 1cm.

with an iron.

Press the seam (1cm)

Bottom fabric


(front/outer side)

With front/outer sides facing

outer fabric A together.

each other, sew the zipper and


 With front/outer sides facing each other, sew together both side edges and the bottoms.






For the lining fabric, fold the opening seam first for 1cm and sew.

5. Put together the outer fabric and lining fabric. Using a blind stitch, sew together the zipper and lining fabric.





## □ Outer Fabric A 40cm (110cm width)

- □ Outer Fabric B 40cm (110cm width)
- □ Lining Fabric 40cm (110cm width)
- ☐ Fusible Interfacing 40cm (90cm width)
- □ Coil Fastener (zipper) 30cm one piece

Fabric shown for this sample: Outer Fabric A - Framework JG41900-902 (A)
Outer Fabric B - Framework JG41900-900 (C)

## **Cutting Layout**

**Materials** 

All measurements are in centimeters (cm).

Measurements include seam allowance. 

\*\*All seam allowances 1cm.

