Pocket

(FrS)

Center fabric (FrS)

③ Baste both ends.

4 As in 16, attach

the side fabric (No

tag or frills). Press

2. Make the back outer fabric

① With the front sides facing

each other, sew the top and

Pocket

bottom end of the pocket fabrics



Shoulder Bag with Frills

The craft projects and works featured in kokka-fabric.com are strictly for personal use and enjoyment Please refrain from selling handmade items using the same exact design (including the pieces made in different fabrics) featured in kokka-fabric.com.

(5) Baste the frill on the center fabric.

Center

④ Check the

balance and attach the tag.

Instructions Front Side - (FrS), Reverse Side (RvS)

3 Pull the thread

1. Make the front outer fabric

of the frill fabric in three and sew.

① Fold one of the long ends

Frill (FrS)

Design & work: Yui Tamaki

Size: 19cm (I) 40cm (w-opening side)

Materials & Tools

☐ Fabric (Outer fabric, Pocket, Frill, Shoulder strap): 110cm wide×70cm

(RvS) fabric ② Sew with from ② to shrink to down the seam to (FrS) (FrS) (Lining fabric, Zipper tab fabric): 110cm×30cm rough stitches. the specified dimension. the side fabric side ☐ Fusible interfacing (heavy weight) 90cmx25cm · Make two pieces. and apply stitches. Side fabric Frill (RvS) □ Double slide zipper: One piece (length 40cm) ② Turn the pocket inside out. Frill (FrS) (FrS) □ Tag: One piece Place it over the center fabric 3. Attach the zipper and sew the bottom end. Side fabric Fabric shown for this sample: (FrS) 1) Baste the zipper to the lining fabric. (Outer fabric, Pocket, Frill, Shoulder Strap) echino EKX-97030-32E 2 With the front sides facing each other, sew together (Lining fabric, Zipper tab fabric) echino solid JG-95410-10K Zipper (FrS) the ① and front outer fabric at the top opening side. Center fabric (FrS) 0.3 - (Tabilitian 0.7 **Cutting Layout Pattern** ⑥ With the front sides facing each ⑦ Press down the seam to the Linina Front other, sew together the piece from center fabric and apply stitches. Unit: Centimeters (cm) Add 1cm seam allowance unless fabric outer fabric 3 As in 12, attach the other (5) and side fabric. otherwise stated. (FrS) (RvS) side of the zipper to the lining Adhere fusible interfacing on the back 6. Finish the bag fabric and back side of the 4. Make the outer bag and lining bag of the lining fabric. outer fabric. Center fabric Opening for turning 12 Zipper (RvS) 0.8 Fold line Zipper tab fabric (RvS) Lining fabric (RvS) Zipper tab fabric Lining 2 Fold the ends of 30 Side fabric/ Lining fabric fabric-① Open the zipper. With the Shoulder strap the zipper tab fabric (raw edge all around) Shoulder strap \\$₽₫ 13 19 15 (FrS) front sides facing each other, and place it over the sew together the outer fabrics end of the zipper Pocket (i) Fold both ends of the and lining fabrics respectively, as shown. opening into a triangle. Opening_{0.8} leaving an opening for turning Insert the shoulder strap Lining bág and side openings. into the opening and sew (FrS) Lining bag together. Cut off excess zipper. 15 (FrS) Back Zipper tab fabric (FrS) outer fabric (RvS) -3 Fold Pocket Pocket Front outer fabric (FrS) /Center Center fabric fabric Shoulder strap ⑤ Turn it inside out and align the shape. 2) Turn it inside out and close the opening for turning. Lining bag (FrS) Side Side Side Side Lining bag fabric/ fabric/ fabric/ \fabric/ 70 Raw (FrS) 5. Make the shoulder strap edge 4 Fold in two and Shoulder apply blind stitches. strap 1 With the front sides facing each 2 Turn it inside out and other, sew two pieces together. fold both ends in three. Shoulder strap Raw edge Outer bag front 6 Shoulder strap 110 all around (RvS) Zipper tab fabric (FrS) (FrS) Lining bag • Repeat the same - 110 process on the other side.