Fusible i

Front body B side

(FrS)

and sew.

201 ______

③ Turn over the bias

the pocket opening

binding strip and wrap

(FrS)

nterfacing

Bias binding

strip (FrS)

(2cm×2cm)

A-Line Reversible Dress

kokka-fabric.com

interfacing

(2cm×6cm)

The craft projects and works featured in kokka-fabric.com are strictly for personal use and enjoyment Please refrain from selling handmade items using the same exact design (including the pieces made in different fabrics) featured in kokka-fabric.com.

Back body

B side (RvS)

(FrS)

② With the front sides facing

each other, sew together the

pocket and bias binding strip.

Instructions Front Side - (FrS), Reverse Side (RvS)

1. Adhere fusible interfacing

Adhere fusible interfacing on the buttonhole and button attachment

2. Make the pocket

(FrS)

of the B side.

position on the front and back body

1) Fold the tuck

and baste it.

Design & work: Naomi Nohara (lepolepo)

Size: Height 90cm size Length 47cm Body width 31cm



Materials

- ☐ Fabric (Body Side A, Bias Binding Strip): 110cm wide×90cm
- ☐ Fusible interfacing: 8cmx6cm

Fabric shown for this sample:

(Body - Side B): PIKKU SAARI EGX-4004-2C

90

Cutting Layout

Add 1cm seam allowance unless specified otherwise.

Front body Side A

(FrS)

Front body

Pocket opening

Pocket

raw edge

Bias binding strip

Back body

Raw edge all around

2 Turn it inside out using the opening. Fold the seam of the opening inward and apply top stitches.



Pattern



