2cm and sew.



Gathered Neck Blouse and Tucked Skirt Matching Set

Design & work: Yoko Kato

Size:

Blouse length 53cm Skirt length 84cm

Materials

- □ Fabric: 106cm wide x 4m
- ☐ Elastic Tape: Waist measurement + 2cm (2.5cm wide)

Fabric shown for this sample: kuiskaus EGX-63000-3B

Pattern Cutting Layout Unit: cm Add 1.5cm seam unless otherwise specified Raw edge Back bodv Fold Back center Sew up to here 53 Front center fold line Raw edge fold line Blouse `Facing Blouse Back body Front body • 39.5 -— 39.5 — Front skirt Bias binding strip Raw edge (one piece) all around acing3. 2.5 Opening for Raw edge elastic tape 'n Tuck - Sew up (left side) Facing to here Front and back Raw center fold line Back skirt edge Front Front and Back line body 48 - 106

kokka-fabric.com

The craft projects and works featured in kokka-fabric.com are strictly for personal use and enjoyment Please refrain from selling handmade items using the same exact design (including the pieces made in different fabrics) featured in kokka-fabric.com.

Instructions Front Side - (FrS), Reverse Side (RvS) <Blouse> Bias binding strip 1 Apply zigzag stitches on all (FrS) 3 Finish the neckline. the seams, except for the seams Fold the seam in three of the front and back body Back body $(0.7cm \rightarrow 0.8cm)$ and sew. neckline and hem. (RvS) 0.1Front body Back body 2 With the front sides (RvS) (RvS) facing each other. Sew the armhole. sew together the front Sew up to here body and back body at Bias binding strip the shoulder. Press (FrS) Press the side seam 4 With the front sides the seam open. Front body open naturally. facing each other, (FrS) .0.1 sew together the front body and back body at the sides, up to where the opening stops. Body Press the seam open. (FrS) 4 Press the seam from 1 open. 6 Fold the seam of the hem With the front sides facing each other, in three (1cm \rightarrow 1cm) and sew. sew together with 3. (5) With the front sides facing outside, 3 Back body fold the bias binding strip in four and 2 With rough stitches, sew two place 4 in-between and sew. (RvS) 1 With the front sides facing stitch lines on both front and back. Back body each other, fold the bias binding (RvS) strip in half and sew. Back body (RvS) (RvS) (FrS) Back center Front body (FrS) Bias binding strip (RvS) Front body Front body (FrS) (FrS) Bias binding strip 3 Pull the thread from 2. Shrink (FrS) the fabric to 35cm (front neckline) and to 31cm (back neckline). ① With the front sides facing outside, fold the center of the tuck and sew 2 Put together the center of the tuck up to where indicated. and stitch line from 1 and sew both <Skirt> 5 Fold the facing and sew. Tuck 2 ends to secure. Tuck center Facing (FrS) Back skirt ·(🛕) (RvS) 1 Apply zigzag stitches 4 Apply stitches around Facing on the seam of the facing the opening for (FrS) (RvS) the elastic tape. and sides. Sew up (RvS) to here 7 Insert the elastic 3 With the front sides-2 Sew the tucks. tape through facing each other, the opening. sew together the front skirt and back skirt at Apply stitches. the sides. Press 7 the seam open. Front skirt Facing (FrS) (On the left side, (FrS) leave an opening for the elastic tape). Left side Back skirt Front skirt Insert the elastic, (RvS) (RvS) overlap the ends by

©Fold the seam of the hem in three (1cm \rightarrow 1.5cm) and sew.